

ADDENDUM NO 01

to

Bid 030-12 Walking Floor Trailer

City of Fairhope

The bid documents for this Bid shall be amended, revised and changed in the following particulars provided by Public Works Department:

Delete: Page titled SPECIFICATIONS in ITEM IV

Replace with attached page: SPECIFICATIONSrev1

Responders are to sign and include signed Addendum No.1 with submitted bid documents.

Acknowledged:

Company

By

Daniel P. Ames
Purchasing Manager
City of Fairhope
Posted: 10-10-2012

SPECIFICATIONSrev1

LIVE FLOOR TRAILER SPECIFICATIONS

BODY CLASSIC BODY STYLE

Length	45'
Width	102"
Height	102" (111 cubic yd capacity)
Side Sheet	175 aluminum 5454 H34
Side Post	24" Centers
Catwalk	Yes
Top Rail	4 x 9 extruded aluminum
Crossmembers	5" alum I beam on 12" centers ABS
Lower Rail	6" boxed alum extrusion
Nose/Bulkhead	.250 Aluminum
Ladders	steps, front & rear, Drivers side
Longitudinal/Frame	6" aluminum Z rail
Tarp Rod/Bar	No Tarp Rod
Flaps	1/2" rubber, anti-spray, anti-sail
Marker Lights	3 per side, std
Center Turn Signal	standard
Light Panel	outboard, with 3" eyebrow
Hose Hanger	standard

SUSPENSION / CHASSIS

Suspension	Reyco 21B (OR EQUIVALENT)
Type	52,000 lb, 4 spring-9-Leaf
Axles	25,000lb capacity
Hubs	Steel
Drums	Cast
Width	102" wide
Brakes	16 1/2 x 7", air actuated, auto slacks
WABCO	2S/1M (min.fed. std)
Wheels 1	0 hole steel disc (8) hub piloted
Size	22.5 X 8.25
Tires	Std Radial
Size	11RX22.5
Kingpin Setting	36"
Dollies	Holland Mark V, 2-speed LG (OR EQUIVALENT)
Tire Carrier	yes
Tow Hooks	Included
Coupler Plate	3/8" steel
Paint	Automotive Grade Metallic

TAILGATE

Height	102"
Thickness	.160 aluminum
Hinge	Single Acting Barndoor, 4 hinges On Curbside
Air or Manual	air, dual lathes
Safety Latches	1, Standard
Gate Guide	Standard
Crosspipe	3, Standard
Bumper	ICC type
Push Blocks	Push Bumper & 2-tow Hooks